

IMPACT DRIVER

Main Features

1. For various types of screws
2. Aluminum window sash
3. Furniture and other wooden applications.
4. Assembly for motorbikes and light vehicles
5. Disassembly/fixing of fenders, bumpers, and interiors.



■ 1/4" (6.35mm) HEX.

KW-50S

Oil Bath Impact Driver
Double Hammer

Drive Size	1/4" Hex	6.35 mm
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Length (w/o socket)	7-1/4 in.	184.0 mm
Weight (w/o socket)	1.7 lbs.	0.77 kg
Air Consumption (normal)	7.1 c.f.m.	0.20 m ³ /min
Hose Size	1/4 in.	6.5 mm



For Super Soft Joint

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 1/4" (6.35mm) HEX.

KW-50PD

Double Hammer

Drive Size	1/4" Hex	6.35 mm
Free Speed	10,000 r.p.m.	
Recommended Torque	1.5-20 ft-lb	2-30 Nm
Length (w/o socket)	6-3/4 in.	171.0 mm
Weight (w/o socket)	1.4 lbs.	0.64 kg
Air Consumption (normal)	6.4 c.f.m.	0.18 m ³ /min
Hose Size	1/4 in.	6.5 mm



※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 1/4" (6.35mm) HEX.

KW-50H

Oil Bath Impact Driver
Double Hammer

Drive Size	1/4" Hex	6.35 mm
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Length (w/o socket)	7-1/4 in.	184.0 mm
Weight (w/o socket)	1.7 lbs.	0.77 kg
Air Consumption (normal)	7.1 c.f.m.	0.20 m ³ /min
Hose Size	1/4 in.	6.5 mm



For Soft Joint

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 1/4" (6.35mm) HEX.

KW-7PD

Oil Bath Impact Driver
Double Hammer

Drive Size	1/4" Hex	6.35 mm
Free Speed	8,800 r.p.m.	
Impact Per Min.	2,500 i.p.m.	
Recommended Torque	7-50 ft-lb	10-70 Nm
Length (w/o socket)	5-15/16 in.	150.0 mm
Weight (w/o socket)	2.2 lbs.	1.0 kg
Air Consumption (normal)	10.6 c.f.m.	0.30 m ³ /min
Hose Size	1/4 in.	6.5 mm



※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 1/4" (6.35mm) HEX.

KW-50

Oil Bath Impact Driver
Double Hammer

Drive Size	1/4" Hex	6.35 mm
Free Speed	10,500 r.p.m.	
Impact Per Min.	3,000 i.p.m.	
Recommended Torque	1.5-20 ft-lb	2-27 Nm
Length (w/o socket)	7-1/4 in.	184.0 mm
Weight (w/o socket)	1.7 lbs.	0.77 kg
Air Consumption (normal)	7.1 c.f.m.	0.20 m ³ /min
Hose Size	1/4 in.	6.5 mm



For Hard Joint

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.