

**Heavy-duty grinders for tough applications**

- Side exhaust with noise reduction system
- Great power/weight ratio


**Model MYG-25**

- For Grinding Wheel 58 mm
- Compact and lightweight type



**Model MYG-40**

- For Grinding Wheel 100 mm
- Powerful type



**Model MG-40**

- Lever switch type
- Depressed center wheel 100 mm



**Model MG-40** Non-CE

- Ring switch type
- Depressed center wheel 100 mm



**Specifications**

Model	MYG-25	MYG-40	MG-40 Lever Type	MG-40 Ring Type
Air Pressure	MPa (kgf/cm <sup>2</sup> ) 0.6 (6)			
Air Consumption	m <sup>3</sup> /min 0.42 (No-load)	0.50 (No-load) 0.69 (Load)		0.50 (No-load)
Free Speed	min <sup>-1</sup> (rpm) 19000	13000		
Depressed Center Grinding Wheel	mm 58	100		
Inlet Size	Rc 1/4		Rc 3/8	
Mass (Weight)	kg 0.6	1.5	1.6	1.4
Accessories Included	<ul style="list-style-type: none"> <li>• 5 mm Hex. Socket Screw Key</li> <li>• 19 mm Single Ended Spanner</li> <li>• Grinding Wheel GS #80 x 58</li> <li>• Bushing R 1/4 x NPT 1/4</li> </ul>	<ul style="list-style-type: none"> <li>• 5 mm Hex. Socket Screw Key</li> <li>• 6 mm Hex. Socket Screw Key</li> <li>• Bushing R 3/8 x NPT 3/8</li> </ul>	<ul style="list-style-type: none"> <li>• 5 mm Hex. Socket Screw Key</li> <li>• 6 mm Hex. Socket Screw Key</li> <li>• Spanner 19</li> <li>• Bushing R 3/8 x NPT 3/8</li> </ul>	<ul style="list-style-type: none"> <li>• 5 mm Hex. Socket Screw Key</li> <li>• 6 mm Hex. Socket Screw Key</li> <li>• Spanner 19</li> <li>• Bushing R 1/4 x NPT 3/8</li> </ul>

**Model MYG-50**

- Lever switch type
- For Grinding wheel 125 mm
- Heavy grinding type



**Model MYG-70**

- Lever switch type
- For Grinding wheel 180 mm
- Heavy grinding type



**Model MYG-70** Non-CE

- Ring switch type
- For Grinding wheel 180 mm
- Heavy grinding type



**Specifications**

Model	MYG-50	MYG-70 Lever Type	MYG-70 Ring Type
Air Pressure	MPa (kgf/cm <sup>2</sup> ) 0.6 (6)		
Air Consumption	m <sup>3</sup> /min 0.75 (No-load)	0.70 (No-load) 0.95 (Load)	
Free Speed	min <sup>-1</sup> (rpm) 11000	7600	
Depressed Center Grinding Wheel	mm 125	180	
Inlet Size	Rc 3/8		
Mass (Weight)	kg 2.5 (with handle)	2.4 (with handle)	
Accessories Included	<ul style="list-style-type: none"> <li>• Handle (anti-vibration type)</li> <li>• 4 mm Hex. Socket Screw Key</li> <li>• 6 mm Hex. Socket Screw Key</li> <li>• Pin Face Wrench</li> <li>• Bushing R 3/8 x NPT 3/8</li> </ul>	<ul style="list-style-type: none"> <li>• Handle</li> <li>• 6 mm Hex. Socket Screw Key</li> <li>• 10 mm Hex. Socket Screw Key</li> <li>• Bushing R 3/8 x NPT 3/8</li> </ul>	