

N



MODEL [OUT-IN] Metric size

CODE	MODEL	Outer Dia mm	Inner Dia mm	Packing Unit(m)	The radius of curvature (mm)	Burst pressure (kg/cm ²)	W.G(g) g/m	(mm)	
								C	BK
413400003201	N-03020	3	2	200	20	150	7	o	o
413400004201	N-04020	4	2	200	20	150	9	o	o
413400004251	N-04025	4	2.5	200	20	60	9	o	o
413400006400	N-06040	6	4	100	30	90	17	o	o
413400008600	N-08060	8	6	100	48	60	23	o	o
413400010800	N-10080	10	8	100	60	50	36	o	o
413400012900	N-12090	12	9	100	72	60	52	o	o

Common Precautions of Tube Series

Never fail to check the following

⚠ WARNING

1. Never use for applications other than air. Using for applications other than air, it causes water leakage by breakage or crack of tube from chemical reaction.
2. Installing the tube near heater, it causes exposition of tube from heat.
3. Scarring the tube with a gimlet or a pin, it causes breakage of tube.
4. Twisting, screwing or bending the tube, it causes breakage or leakage of air.
5. Never use tube in a place of rising spatter.

⚠ CAUTION

1. Be sure to keep the radius of curvature of tube per size.
2. Be sure to leave a margin for unexpected additional length of tube when piping.
3. Be sure to check that the section of tube is at a right angle(90) or tube is oval, not round.